



**Adhesives**

The only adhesive line developed exclusively for fiber optics

**1. MATERIAL IDENTIFICATION**

Product Name:



Emergency Phone: For product emergencies involving spill, leak, fire, exposure, or accident call CHEMTREC at (800) 424-9300. For all other inquires call **Fiber Optic Center™, Inc.** at (800) 473-4237.

**2. COMPOSITION**

Exposure Limits

Hazardous Components	CAS No.	Percent	ACGIH TLV-TWA	OSHA PEL
Epoxy Resin Blend	Proprietary	< 100	N.E.	N.E.

Abbreviations: N.E. = Not Established

**3. HEALTH HAZARDS IDENTIFICATION**

Primary Routes of Exposure: Eyes: Yes      Skin: Yes      Inhalation: No

Eye Contact: May cause irritation.

Skin Contact: May cause irritation, allergic reactions, and sensitization.

Inhalation: Effects are not known.

Ingestion: Effects are not known.

Other: Preexisting skin and eye disorders may be aggravated by exposure to this product. Individuals with preexisting skin or lung allergies may experience increased allergy symptoms upon exposure to this product.

**4. FIRST AID MEASURES**

Eyes: Flush eyes thoroughly with water for 15 minutes while holding eyelids open. Seek medical attention.

Skin: Remove contaminated clothing, wipe excess from skin, and flush the affected area with water. Follow by washing with soap and water. Wash contaminated clothing thoroughly before reuse. If irritation persists after the affected area is washed, obtain medical attention. Contaminated leather articles, such as shoes, cannot be decontaminated and should be destroyed.

Inhalation: Remove to fresh air, and provide oxygen or artificial respiration if needed. Obtain medical attention.

Ingestion: Do NOT induce vomiting. Obtain medical attention.

**5. FIRE FIGHTING MEASURES**

FLAMMABLE PROPERTIES

Flash Point: > 200°F, estimated

Explosive Limits: Not determined

Auto-Ignition Temperature: Not determined

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, aldehydes, acids, and other organic substances

EXTINGUISHING MEDIA and FIRE FIGHTING INSTRUCTIONS

When sufficiently large quantities are present, firefighters should be equipped with full bunker gear, including a positive pressure, NIOSH approved, self-contained breathing apparatus. Fire-exposed containers may be cooled with water.

Extinguishing Media: Use carbon dioxide, dry chemical, or an appropriate foam.

ÅngströmBond® is a REGISTERED TRADEMARK of FIBER OPTIC CENTER, INC., NEW BEDFORD MA, USA

**Fiber Optic Center™, Inc.** MAKES NO EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS OR OTHERWISE, with respect to its products. In addition, while the information herein is believed to be reliable, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. All recommendations or suggestion for use are made without guarantee -- inasmuch as conditions of use are beyond our control. The properties given are typical values, and are not intended for use in preparing specifications. Users should make their own test to determine the suitability of this product for their own purposes.

Rev. A 3/2000

**Fiber Optic Center™, Inc.**, 23 Centre Street, New Bedford, MA, 02740-6322, USA E-mail: sales@focenter.com  
Toll Free: (800) IS-FIBER or (800) 473-4237 • Phone: (508) 992-6464 • Fax: (508) 991-8876 • Website: www.focenter.com

THE ONLY ADHESIVE LINE DEVELOPED EXCLUSIVELY FOR FIBER OPTICS

## **6. ACCIDENTIAL RELEASE MEASURES**

Ventilate the spill area, and evacuate if necessary. Shut off the source of the leak if it is safe to do so. Remove all ignition sources. Dike and contain large spills. Absorb with clay, sand, or another suitable material, and dispose of properly. Clean-up personnel should use adequate protective equipment.

## **7. HANDLING AND STORAGE**

Store in a cool, dry place. Keep away from ignition sources and high temperatures. Avoid contact with incompatible materials. Wear protective eyewear, chemical-resistant gloves, and other protective clothing as appropriate. Some curing agents, if mixed with this product in sufficiently large quantities, can cause exothermic reactions and runaway polymerization, yielding fumes which vary widely in composition and toxicity. Do not breathe fumes.

## **8. EXPOSURE CONTROLS AND PERSONAL PROTECTION**

**Engineering / Ventilation Controls:** General ventilation may be acceptable under most conditions, although local ventilation is required to control exposure whenever vapors, mists, or dusts are generated. Eye wash stations should be readily available.

**Respiratory Protection:** When local ventilation is unavailable and airborne limits are exceeded, a NIOSH-approved respirator, a supplied-air respirator, or a self-contained breathing apparatus is required.

**Skin Protection:** Impervious gloves and protective clothing should be worn as necessary.

**Eye Protection:** Chemical splash goggles with side shields should be worn as appropriate.

## **9. STABILITY AND REACTIVITY**

**Chemical Stability:** Stable under normal conditions and use.

**Conditions and Materials to Avoid:** Keep away from ignition sources and high temperatures. Reacts with acids, bases and strong oxidizing agents.

**Hazardous Decomposition Products:** Carbon monoxide, carbon dioxide, aldehydes, acids, and other organic substances.

**Hazardous Polymerization:** Will not occur.

## **10. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance/State:</b>	Pale yellow liquid	<b>Boiling Point:</b>	Not determined
<b>Odor:</b>	Not determined	<b>Freezing Point:</b>	Not determined
<b>pH:</b>	Not determined	<b>Specific Gravity:</b>	Not determined
<b>Vap. Pressure (mmHG):</b>	Not determined	<b>Solubility in Water:</b>	Negligible
<b>Vap. Density (air = 1):</b>	Not determined		

## **11. TOXICOLOGICAL INFORMATION**

This product is not known to have undergone toxicological testing.

## **12. DISPOSAL CONSIDERATIONS**

Keep out of surface waters, sewers, and waterways entering or leading to surface waters. Notify authorities if any exposure to the environment occurs or is likely to occur. Utilize an appropriate disposal facility, in compliance with applicable federal, state, and local environmental control regulations.

**ÅNGSTRÖMBOND®** IS A REGISTERED TRADEMARK OF FIBER OPTIC CENTER, INC., NEW BEDFORD MA, USA

**Fiber Optic Center™, Inc.** MAKES NO EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS OR OTHERWISE, with respect to its products. In addition, while the information herein is believed to be reliable, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. All recommendations or suggestion for use are made without guarantee -- inasmuch as conditions of use are beyond our control. The properties given are typical values, and are not intended for use in preparing specifications. Users should make their own test to determine the suitability of this product for their own purposes.

Rev. A 3/2000

**Fiber Optic Center™, Inc.**, 23 Centre Street, New Bedford, MA, 02740-6322, USA E-mail: sales@focenter.com  
Toll Free: (800) IS-FIBER or (800) 473-4237 • Phone: (508) 992-6464 • Fax: (508) 991-8876 • Website: www.focenter.com

THE ONLY ADHESIVE LINE DEVELOPED EXCLUSIVELY FOR FIBER OPTICS

**13. TRANSPORTATION INFORMATION**

DOT / IATA Proper Shipping Name: Not regulated.

**14. REGULATORY INFORMATION****TSCA**

The chemical components of this product are included in the TSCA Chemical Substance Inventory, as required.

**SARA TITLE III**

## Section 313 – Toxic Chemicals

Pursuant to Section 313, this product does not contain any chemicals in a concentration equal to or greater than the *de minimis* level.

## Section 311/312 – Hazard Categories

Fire Hazard:	No	Immediate (Acute) Health Hazard:	Yes
Reactivity Hazard:	No	Delayed (Chronic) Health Hazard:	No
Sudden Release of Pressure Hazard:	No		

<b>NFPA Hazards:</b>	Health: 2	Flammability: 1	Reactivity: 0
<b>HMIS Hazards:</b>	Health: 2	Flammability: 1	Reactivity: 0

**STATE REGULATIONS / RIGHT TO KNOW****California Proposition 65:** This product contains a chemical or chemicals which are recognized by the State of California to cause cancer, birth defects, or other reproductive harm.

**Fiber Optic Center™, Inc.** urges each customer or recipient of this MSDS to study it carefully in order to become aware of and understand the hazards associated with the product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology, and/or fire prevention, as necessary to use and understand the data contained in this MSDS.

To promote safe handling, customers and recipients should: 1 – notify their employees, agents, contractors, and others whom they know or suspect will use this material or the information in this MSDS and any other information regarding hazards or safety; 2 – furnish this same information to each of their customers for the product; and 3 – request their customers to notify their employees, customers and other users of the product of this information.

The information contained herein is based on the data available to **Fiber Optic Center™, Inc.**, and is believed to be correct. However, **Fiber Optic Center™, Inc.** makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained from the use thereof. **Fiber Optic Center™, Inc.** assumes no responsibility for injury from the use of the product described herein.

ÅNGSTRÖMBOND® is a REGISTERED TRADEMARK of FIBER OPTIC CENTER, INC., NEW BEDFORD MA, USA

**Fiber Optic Center™, Inc.** MAKES NO EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS OR OTHERWISE, with respect to its products. In addition, while the information herein is believed to be reliable, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. All recommendations or suggestion for use are made without guarantee -- inasmuch as conditions of use are beyond our control. The properties given are typical values, and are not intended for use in preparing specifications. Users should make their own test to determine the suitability of this product for their own purposes.

Rev. A 3/2000

**Fiber Optic Center™, Inc.**, 23 Centre Street, New Bedford, MA, 02740-6322, USA E-mail: sales@focenter.com  
Toll Free: (800) IS-FIBER or (800) 473-4237 • Phone: (508) 992-6464 • Fax: (508) 991-8876 • Website: www.focenter.com